

1	2	3	4	5	6	7	8	9	10																																		
A								变更履历																																			
	修订	日期	描述		已批准																																						
B																																											
C																																											
D																																											
E								<table><tr><th colspan="3">电机参数@25℃</th></tr><tr><td>电压</td><td>48</td><td>V/DC</td></tr><tr><td>旋向(从出轴看)</td><td colspan="2">CW</td></tr><tr><td>空载转速</td><td>6500±12%</td><td>RPM</td></tr><tr><td>空载电流</td><td>≤0.16</td><td>A</td></tr><tr><td>最大连续转速</td><td>5700±12%</td><td>RPM</td></tr><tr><td>最大连续负载电流</td><td>4.0</td><td>A</td></tr><tr><td>最大连续负载力矩</td><td>186</td><td>mN.M</td></tr><tr><td>负载功率</td><td>111</td><td>W</td></tr><tr><td>绝缘耐压</td><td colspan="2">500V AC/50HZ/5mA/1S</td></tr><tr><td>绝缘电阻</td><td>100/250V DC</td><td>MΩ</td></tr></table>			电机参数@25℃			电压	48	V/DC	旋向(从出轴看)	CW		空载转速	6500±12%	RPM	空载电流	≤0.16	A	最大连续转速	5700±12%	RPM	最大连续负载电流	4.0	A	最大连续负载力矩	186	mN.M	负载功率	111	W	绝缘耐压	500V AC/50HZ/5mA/1S		绝缘电阻	100/250V DC	MΩ
电机参数@25℃																																											
电压	48	V/DC																																									
旋向(从出轴看)	CW																																										
空载转速	6500±12%	RPM																																									
空载电流	≤0.16	A																																									
最大连续转速	5700±12%	RPM																																									
最大连续负载电流	4.0	A																																									
最大连续负载力矩	186	mN.M																																									
负载功率	111	W																																									
绝缘耐压	500V AC/50HZ/5mA/1S																																										
绝缘电阻	100/250V DC	MΩ																																									
F																																											
G	客户	本电机Pb、Cr(VI+)、Cd、Hg、PBBs、PBDEs、DBP、BBP、DEHP、DIBP 10种物质的含量满足RoHS要求。 使用注意事项:1.不可拎着电动机引线拿取电机 2.电机引线出口处请不要用外力 3.避免电机落地及碰撞 4.通电状态下不可插拔电机插头 5.电机分解后不可再组装使用 6.在电机的使用过程中若产生有关专利问题本公司不予保证请贵公司特别注意7.电机的转向依据安装面看																																									
	电气原理图																																										
H				除非另外规定,尺寸单位为“mm”,公差按如下规定				设计		日期	江苏鼎智智能控制科技股份有限公司																																
				线性公差		角度公差		批准		日期																																	
				0~3	±0.2	0~10	±1.5°	标准化		日期	尺寸	A3	页数	11																													
				3~6	±0.5	10~50	±1°	会签		日期																																	
				6~30	±0.8	50~120	±30′	型号	40ZYCC71-1			比例	3:1	版本	A																												
30~120	±1.5	120~400	±15′																																								